

TFS Series – Outdoor Rock Speaker

The TFS speaker series is TIC's world renowned outdoor rock speaker series. Praised for being the most realistic outdoor speaker in the market, the TFS series gives you the look and sound that your outdoor entertainment area needs.

Constructed with aerospace grade multi-layer composite cabinetry, the TFS series speaker is built to withstand most outdoor terrain conditions, with options that offer directional, omni, and stereo sound.

Available in various natural rock finishes: Canyon (CN) and Slate (SL) and White Granite (WG), the TFS outdoor rock speaker, not only looks great, but also comes with the durability and audio fidelity that will keep you satisfied for years to come.



Features:

- Realistic Natural Stone Design
- Directional, Stereo and Omni-Directional sound options
- Weather resistant composite housing
- Security stakes included
- Optional external 70v transformer: SP70vTA
- Color/Finish: Canyon(CN), Slate(SL), White Granite (WG)















TFS6 - 200W 8" PERFORMANCE ROCK SPEAKER

TFS10 - 200W 8" PERFORMANCE ROCK SPEAKER







TFS0 - 75W 4.5" ECONOMY ROCK SPEAKERS (PAIR) TFS5 - 150W 6.5" OUTDOOR ROCK SPEAKERS (PAIR)



TFS12 - 200W 8" DVC STEREO ROCK SPEAKER

TFS14 - 300W 10" PROFESSIONAL ROCK SPEAKER





TFS25 - 200W 8" PROFESSIONAL OMNI ROCK SPEAKER TFS50 - 250W 8" PROFESSIONAL OMNI ROCK

TFS50 - 250W 8" PROFESSIONAL OMNI ROCK SUBWOOFER







| Model | TFS0 | TFS5 | TFS6 | TFS10 |
|-----------------------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| Speaker Type | 2 x co-axial | 2 x co-axial | 1 x co-axial | 1 x co-axial |
| Speaker Per Unit | Pair | Pair | Single | Single |
| Peak Power | 75W | 150W | 200W | 200W |
| Continuous Power | 40W | 65W | 100W | 100W |
| Response Frequency | 77Hz-19kHz | 74Hz-20kHz | 35Hz-19kHz | 35Hz-19kHZ |
| Driver | 5.25" | 6.5″ | 8″ | 8" |
| Tweeter | 1" | 2" | 2" | 2" |
| Impedance | 8Ω | 8Ω | 8Ω | 8Ω |
| Unit Dimension | 8" x 10" x 9" | 12 " x 8" x 10" | 11.9" x 16" x 12.1" | 11.7" x 19.2" x 13.5 " |
| Unit Weight | 5 lbs | 7.5 lbs | 14 lbs | 15 lbs |
| Package Dimension | 9.5" x 9" x 21" | 13.5″ x 13.5″ x 11.25″ | 14" x 19" x 14.7" | 15" x 14.5 " x 21" |
| Package Weight | 11.5 lbs | 16 lbs | 19 lbs | 19 lbs |
| UPC Canyon: Slate: | 7 35120 20008 4 7 35120 20108 1 | 7 35120 21015 1 7 35120 21115 8 | 7 35120 20016 0 7 35120 20116 6 | 7 35120 20010 7 7 35120 20110 4 |
| White Granite: | 7 35120 20208 1 | 7 35120 21215 5 | 7 35120 20216 3 | 7 35120 20210 1 |



| Model | TFS12 | TFS14 | TFS25 | TFS50 |
|---|---|---|---|--|
| Speaker Type | 3-way DVC speaker | 3-way speaker | 1 x co-axial | 1 x co-axial |
| Speaker Per Unit | Single | Single | Single | Single |
| Peak Power | 200W | 300W | 200W | 250W |
| Continuous Power | 100W | 200W | 100W | 125W |
| Response Frequency | 35Hz-19kHz | 27Hz-20kHz | 37Hz-19kHz | 25Hz-200HZ (crossover @ 200Hz) |
| Driver | 8" | 10" woofer 5" mid-range | 8" | 8" |
| Tweeter | 2 x 2" | 2" | 2″ | NA |
| Impedance | $8\Omega/input or 4\Omega in parallel mode$ | 8Ω | 8Ω | 8Ω/input standard 4Ω/input with satellite speakers |
| Unit Dimension | 12.2" x 17.3" x 17.3" | 18.5 " x 21.5 x 18" | 13.5" x 11" x 12" | 20" x 13.5" x 11.5 " |
| Unit Weight | 18.2 lbs | 48 lbs | 24 lbs | 24 lbs |
| Package Dimension | 13.7" x 20" 18.9" | 23" x 26" x 22" | 15" x 15.5" x 14.5" | 15" x 14.5 " x 21" |
| Package Weight | 21.2 lbs | 53 lbs | 26 lbs | 26 lbs |
| UPC Canyon: Slate: White Granite: | 7 35120 21012 0 7 35120 21112 7 7 35120 21212 4 | 7 35120 20514 0 7 35120 20614 7 7 35120 20714 4 | 7 35120 20025 7 7 35120 20125 8 7 35120 20225 5 | 7 35120 20050 3 7 35120 20150 3 7 35120 20250 7 |